

INITIAL Heterogeneous Vinyl

3.5mm(T) x 1.8(W) 20m(L)



Education | Offices | Dance | Public Building | Kindergarten

Suitable for heavy traffic

Intensely compacted surface for improved appearance stability and durability

PU surface treatment for easy maintenance

Anti-bacterial and fungicidal

No wax for life

SAMPLE



🌀 3503 DOVE



🌀 3506 SAND





INITIAL heterogeneous vinyl flooring offers excellent acoustic properties plus good resistance to indentation, abrasion and tearing. With a range of designs that provide outstanding creative opportunities, it is ideal for high-traffic areas in kindergarten, dance, education, office and public building. The surface benefits from PUR treatment means no wax and no polish for life. It also requires less water and detergents for cleaning, providing clear benefits for both the environment and for life cycle costs. INITIAL is also available in compact version.

INSTALLATION

INITIAL vinyl sheet should be stored vertically. Installation should be made in accordance with installation guidelines supplied and regularly updated by our technical department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24 C. All seams must be heat welded using the matching weld rod.

MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleanser, or machine scrubbing with an appropriate pad. Further maintenance instructions are available upon request.

TECHNICAL DATA

DESCRIPTION				
Total thickness	EN 428	mm	3.5mm	5.0mm
Wearlayer thickness	EN 429	mm	0.6mm	0.6mm
Weight	EN 430	g/m ²	3020g/m ²	3250g/m ²
Roll width	EN 426	cm	180cm	180cm
Roll length	EN 426	m	20m	20m
CLASSIFICATION				
Classification	EN 685	class	34-43	34-43
Fire rating	NF P 92-506	--	M2	M2
	EN 13 501-1	--	Class Bfl-S1	Class Bfl-S1
	ASTM E648	--	Class 1	Class 1
	GB 8624-2006	--	GB 8624 B1	GB 8624 B1
Toxic testing	GB 18586-2001	--	Pass	Pass
Electrical resistance	EN 1815	kv	< 2	< 2
	EN1081	Ω	≥10 ⁹	≥10 ⁹
Slip resistance dry	EN 13893	--	≥0.3	≥0.3
Slip resistance wet	DIN 51130	--	R9	R9
PERFORMANCE				
Abrasion group	EN 649	--	Group T	Group T
Dimensional stability	EN 434	%	≤0.40	≤0.40
Residual indentation	EN 433	mm	0.05	0.05
Thermal resistance	EN 12 524	W/(m.K)	0.25	0.25
Colour fastness	EN ISO 105 - B02	degree	≥6	≥6
Chemical resistance	EN 423	--	Good	Good
Castor wheel test	EN 425	--	Suitable	Suitable
Impact sound reduction	EN ISO 717/2	dB	19	21
Flexibility	EN 435	--	Excellent	Excellent
Anti-bacterial and fungicidal	MRSA	--	Very Good	Very Good
	DIN EN ISO 846-A/C	--	Good	Good
Surface treatment			PUR	PUR
Underfloor heating		°C	Suitable max. 28	Suitable max. 28

 (230) 651-2121



Royal Road, Domingue Building, Le Hochet, Terre Rouge



info@neelgroup.mu



www.neelgroup.mu



facebook.com/neelgroup.mu

COMPACT Heterogeneous Vinyl

2mm(T) x2.0(W) 20m(L)



Healthcare | Education | Gym | Retail | Office | Hotels

Suitable for heavy traffic

Intensely compacted surface for improved appearance stability and durability

PU surface treatment for easy maintenance

Anti-bacterial and fungicidal

No wax for life

SAMPLE



2122 WOOD



2201 WOOD



COMPACT

Compact heterogeneous vinyl flooring offers good resistance to indentation, abrasion and tearing. Compact has a plain coloured design, making it ideal for cut design work. The calendared wearlayer is treated with UV coating, anti-glazing treatment, which facilitates ease of maintenance and eliminates the need for acrylic emulsion. Compact is available in 18 colours and made of high quality raw materials, it is ideal for high-traffic areas in education, healthcare, offices, gym and retail.

INSTALLATION

Compact vinyl sheet should be stored vertically. Installation should be made in accordance with installation guidelines supplied and regularly updated by our technical department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24 C. All seams must be heat welded using the matching weld rod

MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleanser, or machine scrubbing with an appropriate pad. Further maintenance instructions are available upon request.

TECHNICAL DATA

DESCRIPTION				
Total thickness	EN 428	mm	3.5mm	5.0mm
Wearlayer thickness	EN 429	mm	0.6mm	0.6mm
Weight	EN 430	g/m ²	3020g/m ²	3250g/m ²
Roll width	EN 426	cm	180cm	180cm
Roll length	EN 426	m	20m	20m
CLASSIFICATION				
Classification	EN 685	class	34-43	34-43
Fire rating	NF P 92-506	--	M2	M2
	EN 13 501-1	--	Class Bfl-S1	Class Bfl-S1
	ASTM E648	--	Class 1	Class 1
	GB 8624-2006	--	GB 8624 B1	GB 8624 B1
Toxic testing	GB 18586-2001	--	Pass	Pass
Electrical resistance	EN 1815	kv	< 2	< 2
	EN1081	Ω	≥10 ⁹	≥10 ⁹
Slip resistance dry	EN 13893	--	≥0.3	≥0.3
Slip resistance wet	DIN 51130	--	R9	R9
PERFORMANCE				
Abrasion group	EN 649	--	Group T	Group T
Dimensional stability	EN 434	%	≤0.40	≤0.40
Residual indentation	EN 433	mm	0.05	0.05
Thermal resistance	EN 12 524	W/(m.K)	0.25	0.25
Colour fastness	EN ISO 105 - B02	degree	≥6	≥6
Chemical resistance	EN 423	--	Good	Good
Castor wheel test	EN 425	--	Suitable	Suitable
Impact sound reduction	EN ISO 717/2	dB	19	21
Flexibility	EN 435	--	Excellent	Excellent
Anti-bacterial and fungicidal	MRSA	--	Very Good	Very Good
	DIN EN ISO 846-A/C	--	Good	Good
Surface treatment			PUR	PUR
Underfloor heating		°C	Suitable max. 28	Suitable max. 28

 (230) 651-2121



Royal Road, Domingue Building, Le Hochet, Terre Rouge



info@neelgroup.mu



www.neelgroup.mu



facebook.com/neelgroup.mu